

# Proximity

Stand alone control system


## HA3020



HA3020

HA3020 is a fully selfcontained proximity access controller , used as stand alone device without personal computer connected

**HEART**



CEFC

ISO 9001 Certified



# Smart Proximity

## Stand Alone Access Control

### Characteristics

- Proximity type reader , read range upto 10cm
- Memory capacity store upto 5000 user records
- Large LCD display ,16 characters×2 lines with back light
- Access mode selectable
  - 1.reading proximity card
  - 2.card data + personal password or main password
  - 3.keyin card data
- Anti-duress function available
- Arm or disarm connected security system
- Patrol function available
- Security function available
- User card can be registered /deleted in batch mode
- Authorize card to be removed once incorrect password key-in five times consecutively.
- Alarm to be activated once incorrect password key-in five times within four minutes.
- Activate alarm status either by force entry , tamper switch, anti-duress , security function or door opened off limit
- Last ten history records available
- Audible key tone for easy operate
- Strike , alarm and duress relay drive time selectable (1-255 seconds)
- Door left open time selectable (1-255 seconds)
- Two-piece enclosure design the reader is patted for weather and hazard proofing
- A separate relay module design , high security provided
- With power saver function , the back light of LCD turn off once there is no operation within three minutes



HA3020

### Specification of HA3020 proximity access control

|                       |   |
|-----------------------|---|
| Model                 | HA3020                                      |
| Reader Type           | Proximity                                   |
| Reader Module Type    | EM.HID.TI                                   |
| Reader Range          | Up to 70 mm with EM ISO - Chip card 125 KHz |
| Display               | 16 characters x 2 lines LCD with backlight  |
| Keypad                | 12 Key ( 0-9, *, # )                        |
| Indicator             | Bi-color LED ( Green / Red )                |
| Memory Buffer         | 5000 cardholders                            |
| Case Material         | ABS (UL 94V-0 )                             |
| Working Voltage       | DC 10 - 15 volt                             |
| Power Consumption     | 300mA Max @12VDC                            |
| Dimension             | 150 ( H ) X 110 ( W ) X 45 ( D ) mm         |
| Weight                | 380 g                                       |
| Operating Temperature | 0°C~50°C                                    |
| Humidity              | 5% - 95% ( no condensation )                |
| Approved              | CE, FCC                                     |

